

K-KOMPAKTZYL SCHWENKTISCH MSQ

Rotary actuator for compact cylinder MSQ

HANSA FLEX

Eigenschappen

max. bedrijfsdruk	0,7 MPa
min. bedrijfsdruk	0.10 MPa
Uitvoering	rack and pinion
Mediumtemperatuur	0 °C to +60 °C
Omgevingstemperatuur	0 °C to +60 °C
Zwenkhoek	0 to 190°
Middelen	Perslucht
Serie	MSQ
Overige gegevens	narrow pivot table unit with low overall height the rotation angle can be adjusted continuously Positioning the housing allow for quick installation the load can be mounted directly on the pivot table Air connections of 2 pages possible



Artikel

Aanduiding	Ø zuiger (mm)	Aansluiting pneumatisch	Maat	Damping	Gewicht per m (kg)
K- 07 55 01 13	6	M 3	1	without, with adjustment bolt	0,075
K- 07 55 01 18	8	M 5	2	without, with adjustment bolt	0,105
K- 07 55 01 21	10	M 5	3	elastic, with adjustment bolt	0,150
K- 07 55 01 26	12	M 5	7	elastic, with adjustment bolt	0,250
K- 07 55 01 11	15	M 5	10	elastic, with adjustment bolt	0,530
K- 07 55 01 16	18	M 5	20	elastic, with adjustment bolt	0,990
K- 07 55 01 19	21	G 1/8	30	elastic, with adjustment bolt	1,290
K- 07 55 01 22	25	G 1/8	50	elastic, with adjustment bolt	2,080
K- 07 55 01 24	28	G 1/8	70	elastic, with adjustment bolt	2,880
K- 07 55 01 09	32	G 1/8	100	elastic, with adjustment bolt	4,090
K- 07 55 01 14	40	G 1/8	200	elastic, with adjustment bolt	7,580
K- 07 55 01 12	15	M 5	10	elastic, with integrated shock absorber	0,540
K- 07 55 01 17	18	M 5	20	elastic, with integrated shock absorber	0,990
K- 07 55 01 20	21	G 1/8	30	elastic, with integrated shock absorber	1,290
K- 07 55 01 23	25	G 1/8	50	elastic, with integrated shock absorber	2,100
K- 07 55 01 25	28	G 1/8	70	elastic, with integrated shock absorber	2,880
K- 07 55 01 10	32	G 1/8	100	elastic, with integrated shock absorber	4,100
K- 07 55 01 15	40	G 1/8	200	elastic, with integrated shock absorber	7,650