# K-W90 DRV AS-FS

Speed controllers, 90°,connection plug, with built-in indicator

## Eigenschappen

| | |
|---|---|
| **max. bedrijfsdruk** | 1 MPa |
| **min. bedrijfsdruk** | 0.10 MPa |
| **Afvoeren** | 1 |
| **Aantal toevoerleidingen** | 1 |
| **Uitlijning weergavevenster** | 0° |
| **Kleur draaiknop** | Blue |
| **Testdruk** | 1,50 MPa |
| **Besturing** | Flow governing |
| **Mediumtemperatuur** | -5 °C to +60 °C (ohne Gefrieren) |
| **Omgevingstemperatuur** | -5 °C bis +60 °C (no freezing) |
| **Middelen** | Perslucht |
| **Materiaal slang** | polyamid, soft polyamid, polyurethane, FEP, PFA |
| **Serie** | AS-FS |
| **Overige gegevens** | large rotary knob with push-lock latch<br>larger free space under the hose<br>Lockable rotary knob, numeric display |



## Artikel

| Aanduiding | Maat | Aansluiting afvoer | Aansluiting toevoer | Uitvoering | Naaldomwentelingen | Gewicht per m (kg) |
|---|---|---|---|---|---|---|
| **K- 07 30 30 54** | 1 | for hose outer-Ø2 mm | outer thread M 5 | with sealing ring | 8 | 0,007 |
| **K- 07 30 30 57** | 1 | for hose outer-Ø3.2 mm | outer thread M 5 | with sealing ring | 8 | 0,007 |
| **K- 07 30 30 55** | 1 | for hose outer-Ø4 mm | outer thread M 5 | with sealing ring | 8 | 0,007 |
| **K- 07 30 30 56** | 1 | for hose outer-Ø6 mm | outer thread M 5 | with sealing ring | 8 | 0,008 |
| **K- 07 30 30 62** | 2 | for hose outer-Ø3.2 mm | outer thread R 1/8 | Teflon coated | 10 | 0,007 |
| **K- 07 30 30 67** | 2 | for hose outer-Ø3.2 mm | outer thread R 1/4 | Teflon coated | 10 | 0,023 |
| **K- 07 30 30 58** | 2 | for hose outer-Ø4 mm | outer thread R 1/8 | Teflon coated | 10 | 0,013 |
| **K- 07 30 30 63** | 2 | for hose outer-Ø4 mm | outer thread R 1/4 | Teflon coated | 10 | 0,023 |
| **K- 07 30 30 59** | 2 | for hose outer-Ø6 mm | outer thread R 1/8 | Teflon coated | 10 | 0,014 |
| **K- 07 30 30 68** | 2 | for hose outer-Ø6 mm | outer thread G 1/8 | surface with sealing ring | 10 | 0,014 |
| **K- 07 30 30 64** | 2 | for hose outer-Ø6 mm | outer thread R 1/4 | Teflon coated | 10 | 0,023 |
| **K- 07 30 30 69** | 2 | for hose outer-Ø6 mm | outer thread G 1/4 | surface with sealing ring | 10 | 0,023 |
| **K- 07 30 30 60** | 2 | for hose outer-Ø8 mm | outer thread R 1/8 | Teflon coated | 10 | 0,015 |
| **K- 07 30 30 65** | 2 | for hose outer-Ø8 mm | outer thread R 1/4 | Teflon coated | 10 | 0,024 |
| **K- 07 30 30 70** | 2 | for hose outer-Ø8 mm | outer thread G 1/4 | surface with sealing ring | 10 | 0,024 |
| **K- 07 30 30 61** | 2 | for hose outer-Ø10 mm | outer thread R 1/8 | Teflon coated | 10 | 0,016 |
| **K- 07 30 30 66** | 2 | for hose outer-Ø10 mm | outer thread R 1/4 | Teflon coated | 10 | 0,025 |
| **K- 07 30 30 71** | 2 | for hose outer-Ø10 mm | outer thread G 1/4 | surface with sealing ring | 10 | 0,025 |
| **K- 07 30 30 72** | 3 | for hose outer-Ø6 mm | outer thread R 3/8 | Teflon coated | 10 | 0,038 |
| **K- 07 30 30 76** | 3 | for hose outer-Ø6 mm | outer thread G 3/8 | surface with sealing ring | 10 | 0,038 |
| **K- 07 30 30 73** | 3 | for hose outer-Ø8 mm | outer thread R 3/8 | Teflon coated | 10 | 0,038 |
| **K- 07 30 30 77** | 3 | for hose outer-Ø8 mm | outer thread G 3/8 | surface with sealing ring | 10 | 0,038 |
| **K- 07 30 30 74** | 3 | for hose outer-Ø10 mm | outer thread R 3/8 | Teflon coated | 10 | 0,029 |
| **K- 07 30 30 78** | 3 | for hose outer-Ø10 mm | outer thread G 3/8 | surface with sealing ring | 10 | 0,029 |
| **K- 07 30 30 75** | 3 | for hose outer-Ø12 mm | outer thread R 3/8 | Teflon coated | 10 | 0,041 |
| **K- 07 30 30 79** | 4 | for hose outer-Ø10 mm | outer thread R 1/2 | Teflon coated | 10 | 0,062 |
| **K- 07 30 30 82** | 4 | for hose outer-Ø10 mm | outer thread G 1/2 | surface with sealing ring | 10 | 0,062 |
| **K- 07 30 30 80** | 4 | for hose outer-Ø12 mm | outer thread R 1/2 | Teflon coated | 10 | 0,064 |
| **K- 07 30 30 83** | 4 | for hose outer-Ø12 mm | outer thread G 1/2 | surface with sealing ring | 10 | 0,064 |
| **K- 07 30 30 81** | 4 | for hose outer-Ø16 mm | outer thread R 1/2 | Teflon coated | 10 | 0,068 |
| **K- 07 30 30 84** | 4 | for hose outer-Ø16 mm | outer thread G 1/2 | surface with sealing ring | 10 | 0,068 |

*Hoewel wij zeer zorgvuldig te werk gaan, kunnen wij fouten niet volledig uitsluiten en daarom niet aansprakelijkheid gesteld worden voor de vermelde gegevens.*