

K-T-RINGSTUECK

T-ring nipples

HANSA FLEX

Eigenschappen

| | |
|---------------------|--------------------|
| Werkdruk | Max. 16 bar |
| Bedrijfstemperatuur | -20 °C to +70°C |
| Materiaal | messing vernikkeld |
| Aandrukkring | Hostaform |
| Spanring | Stainless steel |



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Artikel

| Aanduiding | voor banjobout | voor uitw. slang-Ø | L1 (mm) | L2 (mm) |
|----------------|----------------|--------------------|------------|------------|
| K- 07 40 26 93 | M 5 | 4 mm | 36,0 | 9,0 |
| K- 07 40 26 97 | G 1/8 | 4 mm | 42,0 | 15,0 |
| K- 07 40 26 98 | G 1/8 | 6 mm | 46,0 | 15,0 |
| K- 07 40 26 99 | G 1/8 | 8 mm | 49,0 | 15,0 |
| K- 07 40 26 95 | G 1/4 | 6 mm | 48,0 | 17,0 |
| K- 07 40 26 96 | G 1/4 | 8 mm | 52,0 | 17,0 |
| K- 07 40 26 94 | G 1/4 | 10 mm | 52,0 | 17,0 |
| K- 07 40 27 02 | G 3/8 | 8 mm | 54,0 | 20,0 |
| K- 07 40 27 00 | G 3/8 | 10 mm | 56,0 | 20,0 |
| K- 07 40 27 01 | G 3/8 | 12 mm | 58,0 | 20,0 |