

# LKM HR ST DK

Insteekkoppelingsmof (lucht) met borging

**HANSA FLEX**

## Eigenschappen

<b>Constructie</b>	Snelsluitingskoppelingsmof
<b>Aansluiting 1</b>	BSP-buitendraad cilindrisch
<b>Aansluiting 2</b>	
<b>Werkdruk</b>	max. 12 bar
<b>Debiet lucht</b>	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
<b>Mediumtemperatuur</b>	-20 °C to +70 °C
<b>Behuizing</b>	Aluminium, anodised
<b>Schroefdraad</b>	Nickel-plated brass
<b>Inwendige delen</b>	Stainless steel
<b>Knop, ventiel</b>	Hardened, galvanised steel
<b>Afdichtmateriaal</b>	NBR



## Aanwijzing

Not suitable for hitting / pulsating tools.

Andere gegevens op aanvraag.

## Beschrijving

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

## Artikel

Aanduiding	Aansluitschroefdraad	Aansluiting	Lengte (mm)	SW (mm)
LKM 06 HR ST DK	G 1/4" -19	G 1/4 male	70,5	21
LKM 10 HR ST DK	G 3/8" -19	G 3/8 male	70,0	21
LKM 13 HR ST DK	G 1/2" -14	G 1/2 male	72,5	25