

LKM IR ST DK

Insteekkoppelingsmof (lucht) met borging

HANSA FLEX

Eigenschappen

Constructie	Snelsluitingskoppelingsmof
Aansluiting 1	BSP-binnendraad cilindrisch
Aansluiting 2	
Werkdruk	max. 12 bar
Debiet lucht	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Mediumtemperatuur	-20 °C to +70 °C
Behuizing	Aluminium, anodised
Schroefdraad	Nickel-plated brass
Inwendige delen	Stainless steel
Knop, ventiel	Hardened, galvanised steel
Afdichtmateriaal	NBR



Aanwijzing

Not suitable for hitting / pulsating tools.

Andere gegevens op aanvraag.

Beschrijving

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Artikel

Aanduiding	Aansluitschroefdraad	Aansluiting	Lengte (mm)	SW (mm)
LKM 06 IR ST DK	G 1/4" -19	G 1/4 female	71,5	21
LKM 10 IR ST DK	G 3/8" -19	G 3/8 female	75,5	21
LKM 13 IR ST DK	G 1/2" -14	G 1/2 female	77,5	24