

2 OK VC

Zacisk dwuuszkowy

HANSA FLEX

Właściwości

Zakres stosowania zamocowania do węży nisko- i średniociśnieniowych

Materiał stal

Ochrona powierzchni chromocynkowany z polyskiem



Artykuł

| Oznaczenie | Zakres mocowania (mm) | Szerokość taśmy (mm) |
|-----------------|-----------------------|----------------------|
| 2 OK 3-5 VC | 3,0 - 5,0 | 5,0 |
| 2 OK 3.1-4.1 VC | 3,1 - 4,1 | 3,5 |
| 2 OK 3.5-4.5 VC | 3,5 - 4,5 | 3,5 |
| 2 OK 5-7 VC | 5,0 - 7,0 | 6,0 |
| 2 OK 7-9 VC | 7,0 - 9,0 | 7,0 |
| 2 OK 8-11 VC | 8,0 - 11,0 | 7,0 |
| 2 OK 9-11 VC | 9,0 - 11,0 | 7,0 |
| 2 OK 11-13 VC | 11,0 - 13,0 | 7,0 |
| 2 OK 13-15 VC | 13,0 - 15,0 | 7,5 |
| 2 OK 15-17 VC | 15,0 - 17,0 | 8,0 |
| 2 OK 15-18 VC | 15,0 - 18,0 | 8,0 |
| 2 OK 16-19 VC | 16,0 - 19,0 | 8,0 |
| 2 OK 17-20 VC | 17,0 - 20,0 | 8,5 |
| 2 OK 19-22 VC | 19,0 - 22,0 | 9,0 |
| 2 OK 20-23 VC | 20,0 - 23,0 | 9,0 |
| 2 OK 22-25 VC | 22,0 - 25,0 | 10,0 |
| 2 OK 23-25 VC | 23,0 - 25,0 | 10,0 |
| 2 OK 23-27 VC | 23,0 - 27,0 | 10,0 |
| 2 OK 25-28 VC | 25,0 - 28,0 | 10,0 |
| 2 OK 27-31 VC | 27,0 - 31,0 | 10,0 |
| 2 OK 28-31 VC | 28,0 - 31,0 | 10,0 |
| 2 OK 31-34 VC | 31,0 - 34,0 | 10,0 |
| 2 OK 34-37 VC | 34,0 - 37,0 | 10,0 |
| 2 OK 37-40 VC | 37,0 - 40,0 | 10,0 |
| 2 OK 40-43 VC | 40,0 - 43,0 | 10,0 |
| 2 OK 43-46 VC | 43,0 - 46,0 | 10,0 |

Warianty produktu

2 OK Zacisk dwuuszkowy, galwanizowany

2 OK VA Zacisk dwuuszkowy, stal szlachetna