

Właściwości

| | |
|-------------------------------|--------------------------------------|
| Typ konstrukcji | opaski z gwintem ślimakowym |
| Uzupełnienie typu konstrukcji | śruba z łbem sześciokątnym z rowkiem |
| Norma | DIN 3017 |
| Materiał | stal |
| Ochrona powierzchni | ocynkowany |



Artykuł

| Oznaczenie | Zakres mocowania (mm) | Szerokość taśmy (mm) |
|---------------|-----------------------|----------------------|
| ASK 08-12 A | 8 - 12 | 9,0 |
| ASK 08-14 A | 8 - 14 | 9,0 |
| ASK 10-16 A | 10 - 16 | 9,0 |
| ASK 11-17 A | 11 - 17 | 9,0 |
| ASK 12-20 A | 12 - 20 | 9,0 |
| ASK 13-20 A | 13 - 20 | 9,0 |
| ASK 15-24 A | 15 - 24 | 12,0 |
| ASK 16-25 A | 16 - 25 | 12,0 |
| ASK 19-28 A | 19 - 28 | 12,0 |
| ASK 20-32 A | 20 - 32 | 12,0 |
| ASK 22-32 A | 22 - 32 | 12,0 |
| ASK 25-40 A | 25 - 40 | 12,0 |
| ASK 32-44 A | 32 - 44 | 12,0 |
| ASK 32-50 A | 32 - 50 | 12,0 |
| ASK 38-50 A | 38 - 50 | 12,0 |
| ASK 40-60 A | 40 - 60 | 12,0 |
| ASK 44-56 A | 44 - 56 | 12,0 |
| ASK 50-70 A | 50 - 70 | 12,0 |
| ASK 58-75 A | 58 - 75 | 12,0 |
| ASK 60-80 A | 60 - 80 | 12,0 |
| ASK 68-85 A | 68 - 85 | 12,0 |
| ASK 70-90 A | 70 - 90 | 12,0 |
| ASK 77-95 A | 77 - 95 | 12,0 |
| ASK 80-100 A | 80 - 100 | 12,0 |
| ASK 87-112 A | 87 - 112 | 12,0 |
| ASK 90-110 A | 90 - 110 | 12,0 |
| ASK 100-120 A | 100 - 120 | 12,0 |
| ASK 104-138 A | 104 - 138 | 12,0 |
| ASK 110-130 A | 110 - 130 | 12,0 |
| ASK 120-140 A | 120 - 140 | 12,0 |
| ASK 130-150 A | 130 - 150 | 12,0 |
| ASK 130-165 A | 130 - 65 | 12,0 |
| ASK 140-160 A | 140 - 160 | 12,0 |
| ASK 150-170 A | 150 - 170 | 12,0 |
| ASK 150-180 A | 150 - 180 | 12,0 |
| ASK 160-180 A | 160 - 180 | 12,0 |
| ASK 170-190 A | 170 - 190 | 12,0 |
| ASK 175-205 A | 175 - 205 | 12,0 |
| ASK 180-200 A | 180 - 200 | 12,0 |
| ASK 190-210 A | 190 - 210 | 12,0 |
| ASK 200-220 A | 200 - 220 | 12,0 |
| ASK 200-231 A | 200 - 231 | 12,0 |
| ASK 210-230 A | 210 - 230 | 12,0 |
| ASK 220-240 A | 220 - 240 | 12,0 |
| ASK 226-256 A | 226 - 256 | 12,0 |
| ASK 230-250 A | 230 - 250 | 12,0 |
| ASK 240-260 A | 240 - 260 | 12,0 |
| ASK 250-270 A | 250 - 270 | 12,0 |
| ASK 251-282 A | 251 - 282 | 12,0 |
| ASK 260-280 A | 260 - 280 | 12,0 |



ASK A

Opaska zaciskowa do węży

HANSA FLEX

Artykuł

| Oznaczenie | Zakres mocowania (mm) | Szerokość taśmy (mm) |
|---------------|-----------------------|----------------------|
| ASK 270-290 A | 270 - 290 | 12,0 |
| ASK 277-307 A | 277 - 307 | 12,0 |
| ASK 280-300 A | 280 - 300 | 12,0 |
| ASK 290-310 A | 290 - 310 | 12,0 |

Akcesoria

SCHRAUBENDR Wkrętak, giętki