K-SPIR SCHL DREH VERSCHRAU V

Spiral hose, with swivel adapter and kink protector, braided

Właściwości

Rodzaj przyłącza	with kink protector, swivel type
Temperatura robocza	-40 °C to +74 °C



Wskazówka

Dalsze informacje na zapytanie.

Opis

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Artykuł

Oznaczenie	Gwint	Ø wewn. wąż (mm)	Ø zewn. wąż (mm)	Ø zwój zewnętrzny (mm)	Max. working pressure resistance at 23°C (bar)	maks. długość robocza (m)
K- 07 10 07 43	G 1/4	6,3	9,5	42	14	3,0
K- 07 10 07 44	G 1/4	6,3	9,5	42	14	6,0
K- 07 10 07 45	G 1/4	6,3	9,5	42	14	7,5
K- 07 10 07 46	G 3/8	8,0	12,0	55	14	3,0
K- 07 10 07 47	G 3/8	8,0	12,0	55	14	6,0
K- 07 10 07 48	G 3/8	8,0	12,0	55	14	7,5

Akcesoria

K-DREHBARE VERSCHRAUBUNG	Swivel adapters

Mimo starannego sprawdzenia nie możemy wykluczyć błędów i nie gwarantujemy prawidłowości podanych informacji.