

K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

Właściwości

Ciśnienie robocze	0 - 35 bar, maximum static working pressure (non-pulsating)
przepływ powietrza	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura czynnika	-20 °C to +100 °C
końcówka odblokowująca	Anodised aluminium
sprężyny, pierścień osadczy rozprężny, kule	stain less steel
Materiał uszczelniający	NBR



Wskazówka

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Dalsze informacje na zapytanie.

Opis

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artykuł

Oznaczenie	Przyłącze	Kolor	Długość (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	zielony	45,0	14
K- 07 35 06 81	G 1/4 male	zielony	47,0	17
K- 07 35 06 82	G 1/8 female	zielony	45,0	14
K- 07 35 06 83	G 1/4 female	zielony	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	niebieski	45,0	14
K- 07 35 06 89	G 1/4 male	niebieski	47,0	17
K- 07 35 06 90	G 1/8 female	niebieski	45,0	14
K- 07 35 06 91	G 1/4 female	niebieski	47,0	17
K- 07 35 06 92	G 1/8 male	czerwony	45,0	14
K- 07 35 06 93	G 1/4 male	czerwony	47,0	17
K- 07 35 06 94	G 1/8 female	czerwony	45,0	14
K- 07 35 06 95	G 1/4 female	czerwony	47,0	17