

# K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

**HANSA FLEX**

## Właściwości

Ciśnienie robocze	0 - 35 bar, maximum static working pressure (non-pulsating)
przepływ powietrza	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura czynnika	-20 °C to +100 °C
końcówka odblokowująca	Anodised aluminium
sprężyny, pierścień osadczy rozprężny, kule	stain less steel
Materiał uszczelniający	NBR



## Wskazówka

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Dalsze informacje na zapytanie.

## Opis

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

## Artykuł

Oznaczenie	Przyłącze	Kolor	Długość (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	zielony	45,0	14
K- 07 35 06 81	G 1/4 male	zielony	47,0	17
K- 07 35 06 82	G 1/8 female	zielony	45,0	14
K- 07 35 06 83	G 1/4 female	zielony	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	niebieski	45,0	14
K- 07 35 06 89	G 1/4 male	niebieski	47,0	17
K- 07 35 06 90	G 1/8 female	niebieski	45,0	14
K- 07 35 06 91	G 1/4 female	niebieski	47,0	17
K- 07 35 06 92	G 1/8 male	czerwony	45,0	14
K- 07 35 06 93	G 1/4 male	czerwony	47,0	17
K- 07 35 06 94	G 1/8 female	czerwony	45,0	14
K- 07 35 06 95	G 1/4 female	czerwony	47,0	17