


K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

HANSA FLEX

Właściwości

Ciśnienie robocze	0 - 35 bar, maximum static working pressure (non-pulsating)
przepływ powietrza	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura czynnika	-20 °C to +100 °C
Obudowa	Brass
zawór	Die-cast zinc, nickel-plated
końcówka odblokowująca	Anodised aluminium
sprężyny, pierścień osadczy rozprężny, kule	stain less steel
Materiał uszczelniający	NBR



Wskazówka

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Dalsze informacje na zapytanie.

Opis

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artykuł

Oznaczenie	Przyłącze	Kolor	Długość (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	zielony	57,5	19
K- 07 35 08 02	G 3/8 male	zielony	57,5	19
K- 07 35 08 03	G 1/4 female	zielony	55,5	19
K- 07 35 08 04	G 3/8 female	zielony	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	niebieski	57,5	19
K- 07 35 08 10	G 3/8 male	niebieski	57,5	19
K- 07 35 08 11	G 1/4 female	niebieski	55,5	19
K- 07 35 08 12	G 3/8 female	niebieski	54,5	19
K- 07 35 08 13	G 1/4 male	czerwony	57,5	19
K- 07 35 08 14	G 3/8 male	czerwony	57,5	19
K- 07 35 08 15	G 1/4 female	czerwony	55,5	19
K- 07 35 08 16	G 3/8 female	czerwony	54,5	19