

K-BALGSAUGER 1,5 NBR

Bellows suction pads, round, 1.5 folds, material NBR

HANSA FLEX

Właściwości

Właściwości high rigidity of the upper fold
Soft, tapered sealing lips
Support surfaces on the bottom
high suction power
optimum damping effect
very good adaptation to curved or uneven material

Zakres stosowania Handling of highly uneven parts (e.g. tubes)
Handling of highly sensitive parts



Wskazówka

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy. Dalsze informacje na zapytanie.

Opis

Robust and hard-wearing suction pad with a single sealing lip. Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to compensate varying workpiece heights or uneven surfaces or to handle easily damaged parts. It acts as the connecting element between the vacuum generator and the workpiece.

Dodatkowe informacje

Attention: The price does not include connection nipples. Please order separately.

Artykuł

| Oznaczenie | Łącznik gwint zewnętrzny | Łącznik gwint wewnętrzny | Wysokość montażowa ze złączką, gwint zewnętrzny | Wysokość montażowa ze złączką, gwint wewnętrzny | Ø (mm) |
|----------------|--------------------------|--------------------------|---|---|--------|
| K- 07 45 00 29 | K-07450002 / K-07450004 | K-07450007 | 21 / 22 | 28 | 11,0 |
| K- 07 45 00 31 | K-07450002 / K-07450004 | K-07450007 | 21 / 22 | 28 | 14,0 |
| K- 07 45 00 33 | K-07450002 / K-07450004 | K-07450007 | 24 / 25 | 31 | 16,0 |
| K- 07 45 00 35 | K-07450002 / K-07450004 | K-07450007 | 20,5 / 21,5 | 27,5 | 20,0 |
| K- 07 45 00 37 | K-07450004 | K-07450007 | 29 | 35 | 25,0 |
| K- 07 45 00 39 | K-07450003 | K-07450006 | 31 | 42 | 33,0 |
| K- 07 45 00 41 | K-07450003 | K-07450006 | 32 | 43 | 43,0 |
| K- 07 45 00 43 | K-07450003 | K-07450006 | 38 | 49 | 53,0 |

Akcesoria

K-ANSCHLUSSNIP BALGSAUGER Connection nipples for bellows suction pads, round, 1.5 and 2.5 folds