

K-BALGGREIFER 2,5 SILIKON

Bellows suction pads, round, 2.5 folds, material silicone

HANSA FLEX

Właściwości

Właściwości	Soft, flexible folds Soft, tapered sealing lips Support surfaces on the bottom high suction power optimum damping effect very good adaptation to curved or uneven material
--------------------	---

Zakres stosowania	Handling of highly uneven parts (e.g. tubes) Handling of highly sensitive parts
--------------------------	--



Wskazówka

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy. Dalsze informacje na zapytanie.

Opis

Robust and hard-wearing suction pad with a single sealing lip. Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to compensate varying workpiece heights or uneven surfaces or to handle easily damaged parts. It acts as the connecting element between the vacuum generator and the workpiece.

Dodatkowe informacje

Attention: The price does not include connection nipples. Please order separately.

Artykuł

Oznaczenie	Łącznik gwint zewnętrzny	Łącznik gwint wewnętrzny	Wysokość montażowa ze złączką, gwint zewnętrzny	Wysokość montażowa ze złączką, gwint wewnętrzny	Ø (mm)
K- 07 45 00 46	K-07450001	K-07450005	18,5	23,5	5,0
K- 07 45 00 48	K-07450002 / K-07450004	K-07450007	19 / 20	26	7,0
K- 07 45 00 50	K-07450002 / K-07450004	K-07450007	20 / 21	27	9,0
K- 07 45 00 52	K-07450002 / K-07450004	K-07450007	26 / 27	33	12,0
K- 07 45 00 54	K-07450002 / K-07450004	K-07450007	27 / 28	34	14,0
K- 07 45 00 56	K-07450002 / K-07450004	K-07450007	27 / 28	34	18,0
K- 07 45 00 58	K-07450002 / K-07450004	K-07450007	27 / 28	34	20,0
K- 07 45 00 60	K-07450004	K-07450007	40	46	25,0
K- 07 45 00 62	K-07450003	K-07450006	41,5	52,5	32,0
K- 07 45 00 64	K-07450003	K-07450006	50	61	42,0
K- 07 45 00 66	K-07450003	K-07450006	53	64	52,0

Akcesoria

K-ANSCHLUSSNIP BALGSAUGER Connection nipples for bellows suction pads, round, 1.5 and 2.5 folds