K-DRS MDR 5 M ENTLASTU VENT

»MDR 5« pressure switches, with unloading valve / on/off switch / flange 1/4, without motor protection circuit

Właściwości

Temperatura czynnika	-5 °C to +80 °C
maks. ciśnienie wyłączenia	16 bar
Zdolność łączenia	5,5 kW
rodzaj zestyku	NC (3-pole)
maks. częstotliwość przełączeń	120 (electrical), 600 (mechanical)
rodzaj ochrony	IP 54



Wskazówka

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
Dalsze informacje na zapytanie.

Opis

Three-phase version

Wskazówki do zamówienia

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Dodatkowe informacje

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

Artykuł

Oznaczenie	Przyłącze sprężonego powietrza	Zakres nastawy
K- 07 30 24 25	G 1/2	2,0 - 11,0 bar
K- 07 30 24 27	G 1/2	2,5 - 16,0 bar