
K-SSV BR

Angle-seat valves with piston actuator

Właściwości

ciśnienie różnicowe	0 - 16 bar
Temperatura czynnika	-10 °C to +180 °C
przyłącze powietrza sterującego	G 1/8
temperatura czynnika sterującego	max. +60 °C
temperatura otoczenia	-20 °C to +70 °C
dozwolone ciśnienie statyczne	Max. 16 bar
obudowa zaworu	Bronze
łącznik	Stainless steel
głowica sterująca	Polyamide (glass fibre-reinforced)
tłok	Nickel-plated brass (DN 15 to DN 32), PBT + GF 30% (DN 40 to DN 50)
wrzeciono	Stainless steel
Materiał uszczelniający	PTFE





Wskazówka

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.
Dalsze informacje na zapytanie.

Opis

Angle-seat valves with external pilot control and a self-aligning valve discfor neutral (bronze body) or corrosive (stainless steel body) media. Very high flow due to angled seat design, Water hammer prevented by fluid entry under the disc, Suitable for vacuum operation (low vacuum), NAMUR interface on the piston actuator. 3/2 and 5/2-way valves can be mounted directly.

Dodatkowe informacje

Other versions e.g. for steam on request
Information on max. operating differential pressures apply for air, gas, corrosive aggressive media, water

Artykuł

Oznaczenie	A (mm)	C (mm)	F (mm)	Gwint	maks. różnica ciśnienia roboczego (bar)	min. ciśnienie sterujące	maks. ciśnienie sterujące
K- 07 30 25 24	163,0	153,0	65,0	G 1/2	16	4	10
K- 07 30 25 25	173,0	163,0	75,0	G 3/4	10	4	10
K- 07 30 25 26	191,0	181,0	75,0	G 3/4	16	4	10
K- 07 30 25 27	206,0	196,0	90,0	G 1	11	4	10
K- 07 30 25 28	246,0	236,0	90,0	G 1	16	4	8
K- 07 30 25 29	255,0	245,0	110,0	G 1 1/4	14	4	8
K- 07 30 25 30	270,0	264,0	120,0	G 1 1/2	11	4	8
K- 07 30 25 31	306,0	300,0	120,0	G 1 1/2	16	4	8
K- 07 30 25 32	316,0	311,0	150,0	G 2	10	4	8

Mimo starannego sprawdzenia nie możemy wykluczyć błędów i nie gwarantujemy prawidłowości podanych informacji.