

# K-SCHALLDAEMPFER VA

Stainless steel silencers

**HANSA FLEX**

## Właściwości

|                            |                                   |
|----------------------------|-----------------------------------|
| <b>Ciśnienie robocze</b>   | maks. 8 bar                       |
| <b>Temperatura robocza</b> | -10 °C to +250 °C                 |
| <b>Norma</b>               | G thread acc. to DIN EN ISO 228-1 |
| <b>Materiał</b>            | stal szlachetna 1.4401            |



## Wskazówka

Dalsze informacje na zapytanie.

## Artykuł

| Oznaczenie     | Gwint | A<br>(mm) | B<br>(mm) | RK    |
|----------------|-------|-----------|-----------|-------|
| K- 07 40 13 07 | M 5   | 5,0       | 21,0      | 9 mm  |
| K- 07 40 13 08 | G 1/8 | 7,0       | 29,0      | 12 mm |
| K- 07 40 13 09 | G 1/4 | 9,0       | 33,0      | 15 mm |
| K- 07 40 13 10 | G 3/8 | 9,0       | 39,0      | 19 mm |
| K- 07 40 13 11 | G 1/2 | 9,5       | 48,0      | 23 mm |
| K- 07 40 46 82 | G 3/4 | 11,0      | 58,0      | 30 mm |
| K- 07 40 46 83 | G 1   | 15,0      | 71,0      | 36 mm |