


# K-W90 SVB

## Bulkhead elbow couplings

### Właściwości

<b>Ciśnienie robocze</b>	Dependent on operating temperature; Max. 10 bar (at 20 °C); Max. 1 bar (at 60 °C)
<b>korpus dwuzłączki</b>	Polyamide (PA)
<b>pierścień zaciskowy</b>	Polypropylene (PP)
<b>nakrętka</b>	Polypropylene (PP)



### Wskazówka

Dalsze informacje na zapytanie.

### Opis

Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzene, diesel oil, fuel oil and alkalis. <br>Not suitable for use with acids.

### Artykuł

Oznaczenie	Gwint	dla węża	L1 (mm)	L2 (mm)	RK
K- 07 40 32 78	M 10 x 1	4 mm / 6 mm	43,0	25,0	14 mm
K- 07 40 32 79	M 14 x 1,5	6 mm / 8 mm	53,0	33,0	19 mm
K- 07 40 32 80	M 16 x 1,5	8 mm / 10 mm	58,0	36,0	22 mm
K- 07 40 32 81	M 18 x 1,5	9 mm / 12 mm	67,0	43,0	24 mm