

# K-KONDENSA DRUKODRAIN PLUS

Drain for compressed air condensate

**HANSA FLEX**

## Właściwości

moc przyłączowa filtra	100 m <sup>3</sup> /min
moc przyłączowa sprężarki	10 m <sup>3</sup> /min
moc przyłączowa suszarki	20 m <sup>3</sup> /min



## Wskazówka

Dalsze informacje na zapytanie.

## Opis

Compact and exceptionally reliable, level-controlled drain for compressed air condensate. The condensate enters the integrated collecting tank, in which the level is continuously monitored. When the condensate reaches the maximum mark, the pilot valve opens and the condensate is forced into the discharge line by the system pressure. The valve closes again when the level reaches the minimum mark. Benefits of »drukodrain plus«: No pressure loss, Diaphragm protected by integrated cup filter, Test button for manual outlet, Auto-reset function, Suitable for all condensate types.

## Wskazówki do zamówienia

The following voltages on request: 24 VDC, 24 VAC DC, 24 VAC / 50 Hz, 110 VAC / 50 Hz, 115 V / 50 Hz

## Artykuł

Oznaczenie	Ciśnienie robocze bar	Napięcie
K- 07 25 09 24	0.2 - 16 bar	230 VAC / 50 Hz