

K-DRG DRVS HANSA

Pressure regulators with continuous pressure supply

HANSA FLEX

Właściwości

| | |
|---------------------------|---|
| Ciśnienie wejściowe | Max. 16 bar |
| Zakres temperatury | -10 °C to +50 °C |
| Czynniki robocze | sprężone powietrze |
| Gwint przyłącza | Material: Die-cast zinc |
| Obudowa | Material: Grivory® (PA 66) |
| Przepona | NBR |
| Zużycie własne powietrza | only G3/4, G1 Max. 1.5 l/min (depending on secondary pressure) |
| pomiar wartości przepływu | At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar |



Wskazówka

Dalsze informacje na zapytanie.

Opis

Diaphragm pressure regulators with self-relieving design and excellent flow rates in modern design for mounting side by side. By assembling two or more controllers together, it is possible to supply several working air circuits with different output pressures via a single supply line. The regulator button can be latched and locked.

Wskazówki do zamówienia

The price does not include a key lock. Please order separately.

Artykuł

| Oznaczenie | Gwint | Zakres regulacji | Przepływ (L/min) | A (mm) | B | C (mm) | Typowość |
|----------------|-------|------------------|------------------|--------|----------|--------|----------|
| K- 07 25 02 51 | G 1/4 | 0.1 - 1 bar | 2200 | 52,0 | 128,5 mm | 95,5 | 1 |
| K- 07 25 02 52 | G 1/4 | 0.1 - 2 bar | 2200 | 52,0 | 128,5 mm | 95,5 | 1 |
| K- 07 25 02 53 | G 1/4 | 0.2 - 4 bar | 2200 | 52,0 | 128,5 mm | 95,5 | 1 |
| K- 07 25 02 54 | G 1/4 | 0.5 - 8 bar | 2200 | 52,0 | 128,5 mm | 95,5 | 1 |
| K- 07 25 02 55 | G 1/4 | 0.5 - 10 bar | 2200 | 52,0 | 128,5 mm | 95,5 | 1 |
| K- 07 25 02 56 | G 1/4 | 0.5 - 16 bar | 2200 | 52,0 | 128,5 mm | 95,5 | 1 |
| K- 07 25 02 69 | G 3/8 | 0.1 - 1 bar | 2600 | 52,0 | 128,5 mm | 95,5 | 1 |
| K- 07 25 02 70 | G 3/8 | 0.1 - 2 bar | 2600 | 52,0 | 128,5 mm | 95,5 | 1 |
| K- 07 25 02 71 | G 3/8 | 0.2 - 4 bar | 2600 | 52,0 | 128,5 mm | 95,5 | 1 |
| K- 07 25 02 72 | G 3/8 | 0.5 - 8 bar | 2600 | 52,0 | 128,5 mm | 95,5 | 1 |
| K- 07 25 02 73 | G 3/8 | 0.5 - 10 bar | 2600 | 52,0 | 128,5 mm | 95,5 | 1 |
| K- 07 25 02 74 | G 3/8 | 0.5 - 16 bar | 2600 | 52,0 | 128,5 mm | 95,5 | 1 |
| K- 07 25 02 57 | G 3/8 | 0.1 - 1 bar | 4300 | 63,0 | 149,5 mm | 110,0 | 2 |
| K- 07 25 02 58 | G 3/8 | 0.1 - 2 bar | 4300 | 63,0 | 149,5 mm | 110,0 | 2 |
| K- 07 25 02 59 | G 3/8 | 0.2 - 4 bar | 4300 | 63,0 | 149,5 mm | 110,0 | 2 |
| K- 07 25 02 60 | G 3/8 | 0.5 - 8 bar | 4300 | 63,0 | 149,5 mm | 110,0 | 2 |
| K- 07 25 02 61 | G 3/8 | 0.5 - 10 bar | 4300 | 63,0 | 149,5 mm | 110,0 | 2 |
| K- 07 25 02 62 | G 3/8 | 0.5 - 16 bar | 4300 | 63,0 | 149,5 mm | 110,0 | 2 |
| K- 07 25 02 63 | G 1/2 | 0.1 - 1 bar | 5000 | 63,0 | 149,5 mm | 110,0 | 2 |
| K- 07 25 02 64 | G 1/2 | 0.1 - 2 bar | 5000 | 63,0 | 149,5 mm | 110,0 | 2 |
| K- 07 25 02 65 | G 1/2 | 0.2 - 4 bar | 5000 | 63,0 | 149,5 mm | 110,0 | 2 |
| K- 07 25 02 66 | G 1/2 | 0.5 - 8 bar | 5000 | 63,0 | 149,5 mm | 110,0 | 2 |
| K- 07 25 02 67 | G 1/2 | 0.5 - 10 bar | 5000 | 63,0 | 149,5 mm | 110,0 | 2 |
| K- 07 25 02 68 | G 1/2 | 0.5 - 16 bar | 5000 | 63,0 | 149,5 mm | 110,0 | 2 |

Akcesoria

K-STECKSCHLOSS Key lock

Części zamienne

| | |
|--------------------------|--------------------|
| K-HALTERBAUSATZ HANSA | Holder HANSA |
| K-SCHALTAFELMUTTER HANSA | Nut HANSA |
| K-DICHTSATZ HANSA | Set of seals HANSA |