

K-LP ALU O DUESE

Blow guns die-cast aluminium nickel-plated, without nozzle, Safety

HANSA FLEX

Właściwości

| | |
|----------------------|------------------|
| Ciśnienie robocze | maks. 10 bar |
| Temperatura robocza | -10 °C to +50 °C |
| dysze i przedłużenia | Thread M12x1.25 |



Wskazówka

Dalsze informacje na zapytanie.

Opis

Standard type without nozzle! In combination with the safety nozzles described below, this blow gun meets a wide range of safety requirements. For blowing out and cleaning machines, workpieces, bore holes, hollow parts, etc.

Artykuł

| Oznaczenie | Przylącze | Gwint przylącza |
|----------------|--|-----------------|
| K- 07 10 00 07 | Stem, I.D. 6 | G 1/4 |
| K- 07 10 00 10 | Stem, I.D. 9 | G 1/4 |
| K- 07 10 00 14 | Stem, I.D. 13 | G 1/4 |
| K- 07 10 00 18 | connection nipples for coupling NW 7,2 | G 1/4 |

Akcesoria

| | |
|-----------------------------|--|
| K-ZUBEH LP ALU | Accessories for standard blow guns (series 22) |
| K-FEINSTRAHLDUE LAERMARME M | Low-noise fine-spray nozzles, M12x1.25 connection |
| K-RUNDDUESE LAERMARME M | Low-noise round nozzles, M12x1.25 connection |
| K-FLACHDUESE LAERMARME M | Low-noise flat nozzles, M12x1.25 connection |
| K-STANDARDUESE | Standard nozzle (short version) with Ø 1.5 mm bore |
| K-DAEMPFERDUESE | Silencer nozzle, M12x1.25 connection |
| K-DUESE MIT SCHUTZSCHILD | Nozzle with chip shield, M12x1.25 connection |
| K-VERL DUESE | Extension nozzles |
| K-DRUCKREGULIERDUESE | Regulating nozzle, M12x1,25, Safety |