

# K-ENDVERTEILERDOSEN

End porting box without through-hole thread, PN 15

**HANSA FLEX**

## Właściwości

|                           |                                |
|---------------------------|--------------------------------|
| Ciśnienie robocze         | Max. 15 bar                    |
| moment obrotowy mocowania | 4 Nm                           |
| moment obrotowy gwintu MS | 12 Nm                          |
| Zakres temperatury        | -10 °C to +50 °C               |
| Obudowa                   | Glass fibre-reinforced plastic |
| gwint                     | Brass                          |



## Wskazówka

Dalsze informacje na zapytanie.

## Opis

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

## Artykuł

| Oznaczenie     | Gwint na wejściu | Gwint przyłącza |
|----------------|------------------|-----------------|
| K- 07 40 48 12 | G 1/2"           | 1 x G 1/2       |
| K- 07 40 48 13 | G 1/2"           | 2 x G 1/2       |
| K- 07 40 48 14 | G 1/2"           | 3 x G 1/2       |
| K- 07 40 48 15 | G 3/4"           | 1 x G 1/2       |
| K- 07 40 48 16 | G 3/4"           | 2 x G 1/2       |
| K- 07 40 48 17 | G 3/4"           | 3 x G 1/2       |