

# K-KALIBRIER-TEST UND SERVICE

Calibration, testing and service unit

**HANSA FLEX**

## Właściwości

Wykonanie	Calibration, testing and service unit
dokładność	0,25% FS
temperatura mierzonego czynnika	-20 °C to +80 °C
temperatura otoczenia	-10 °C to +50 °C
części stykające się z mierzonym czynnikiem	CrNi-steel with NBR seal
Obudowa	Die-cast zinc



## Wskazówka

Dalsze informacje na zapytanie.

## Opis

Service case for quick and precise pressure gauge calibration. Suitable for service and maintenance providers of all kinds as well as instrumentation control workshops and quality assurance. Simple operation using four buttons. The high sampling rate (100 measurements / second) guarantees an accurate analysis at the measuring point. Comprised of a CPG500 digital gauge and a CPP40 pneumatic hand test pump with a connecting cable for pressure generation. Operating manual, calibration certificate 3.1, two AA batteries and a protective rubber cap for the housing are enclosed. Includes a plastic emergency case with foam padding.

## Dodatkowe informacje

Further measuring ranges on request

## Artykuł

Oznaczenie	Zakres pomiarowy	Przyłącze
K- 07 20 12 70	-0.95 / +40 bar	G 1/4