

# K-T-STUECKE 130 RD IG

Tees 130, reducing, female/female/female

## Właściwości

powierzchnia	Hot dip galvanised
Zakres temperatury	-20 °C to +300 °C (at 20 bar)
Gwint przyłącza	acc. ISO 7-1
Materiał	Black malleable iron B350-10, design symbol A
Dopuszczenie	DIN DVGW



## Wskazówka

Dalsze informacje na zapytanie.

## Opis

Acc. to DIN EN 10242 (formerly DIN 2950). The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. The fittings are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications.

## Wskazówki do zamówienia

Attention: the thread sizes of Article K-07403783 have changed.

## Dodatkowe informacje

Further types and dimensions on request.

## Artykuł

Oznaczenie	Gwint 1	Gwint 2 T rozgałęźnik zredukowany	Gwint 3
K- 07 40 37 97	Rp 3/8	Rp 1/4	Rp 3/8
K- 07 40 37 83	Rp 1/2	Rp 1/4	Rp 1/2
K- 07 40 37 84	Rp 1/2	Rp 3/8	Rp 1/2
K- 07 40 37 94	Rp 3/4	Rp 1/4	Rp 3/4
K- 07 40 37 95	Rp 3/4	Rp 3/8	Rp 3/4
K- 07 40 37 93	Rp 3/4	Rp 1/2	Rp 3/4
K- 07 40 37 71	Rp 1	Rp 3/8	Rp 1
K- 07 40 37 69	Rp 1	Rp 1/2	Rp 1
K- 07 40 37 70	Rp 1	Rp 3/4	Rp 1
K- 07 40 37 81	Rp 1 1/4	Rp 3/8	Rp 1 1/4
K- 07 40 37 79	Rp 1 1/4	Rp 1/2	Rp 1 1/4
K- 07 40 37 80	Rp 1 1/4	Rp 3/4	Rp 1 1/4
K- 07 40 37 78	Rp 1 1/4	Rp 1	Rp 1 1/4
K- 07 40 37 76	Rp 1 1/2	Rp 3/8	Rp 1 1/2
K- 07 40 37 74	Rp 1 1/2	Rp 1/2	Rp 1 1/2
K- 07 40 37 75	Rp 1 1/2	Rp 3/4	Rp 1 1/2
K- 07 40 37 73	Rp 1 1/2	Rp 1	Rp 1 1/2
K- 07 40 37 98	Rp 1 1/2	Rp 1 1/4	Rp 1 1/2
K- 07 40 37 90	Rp 2	Rp 1/2	Rp 2
K- 07 40 37 91	Rp 2	Rp 3/4	Rp 2
K- 07 40 37 87	Rp 2	Rp 1	Rp 2
K- 07 40 37 89	Rp 2	Rp 1 1/4	Rp 2
K- 07 40 37 88	Rp 2	Rp 1 1/2	Rp 2
K- 07 40 52 02	Rp 2 1/2	Rp 1	Rp 2 1/2
K- 07 40 52 19	Rp 2 1/2	Rp 1 1/4	Rp 2 1/2
K- 07 40 52 03	Rp 2 1/2	Rp 2	Rp 2 1/2
K- 07 40 52 18	Rp 2 1/2	Rp 1 1/2	Rp 2 1/2
K- 07 40 52 05	Rp 3	Rp 2	Rp 3
K- 07 40 52 06	Rp 3	Rp 2 1/2	Rp 3