

# K-WV 3/2 5/2 NAMUR LB

3/2 and 5/2-way spool valves with NAMUR style interface

**HANSA FLEX**

## Właściwości

**Czynniki robocze** Air, neutral gases (filtered)

**Ciśnienie pracy** 1.5 - 8 bar

**Temperatura robocza** +5 °C to +50 °C

**Przyłącze elektryczne** Plug connector PG 9

**Obudowa** Aluminium

**Materiał uszczelniający** NBR



## Wskazówka

Dalsze informacje na zapytanie.

## Opis

Pilot-operated 3/2 and 5/2-way spool valves with threaded ports and a NAMUR style interface. Combines high-quality design with a low price. By adding the conversion plate supplied with each valve, the device can be adapted to a 3/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

## Artykuł

Oznaczenie	Napięcie	Port 1	Przyłącze 3 + 5	DN	Przepływ (L/min)
K- 07 15 00 09	230 V, 50 Hz	G 1/4	G 1/4	8	1370
K- 07 15 00 10	24 V DC	G 1/4	G 1/4	8	1370
K- 07 15 00 11	230 V, 50 Hz	G 3/8	G 1/4	10	1650
K- 07 15 00 12	24 V DC	G 3/8	G 1/4	10	1650