


K-SVKM NW 7,2 SCHL-ANSCHL MS

Quick disconnect couplings DN 7.2, nickel-plated brass, with hose connector, with swivel nut

HANSA FLEX

Właściwości

Ciśnienie robocze	0 - 35 bar, maximum static working pressure (non-pulsating)
przepływ powietrza	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura czynnika	-20 °C to +100 °C
obudowa, tuleja	Nickel-plated brass
zawór	Brass with a bare metal surface
sprężyny, pierścień osadczy rozprężny	Stainless steel 1.4310
sztyfty blokujące	Stainless steel 1.4034
Materiał uszczelniający	NBR



Wskazówka

Dalsze informacje na zapytanie.

Opis

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

Artykuł

Oznaczenie	Przyłącze	Długość (mm)	SW (mm)
K- 07 35 12 67	Hose connection 6 x 4	58,0	21
K- 07 35 07 24	Hose connection 8 x 6	45,0	21
K- 07 35 07 25	Hose connection 10 x 8	49,0	21
K- 07 35 07 26	Hose connection 12 x 9	49,0	21

Elementy dodatkowe

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass