


# K-ELEKTRISCHE ANSCHLUESSE

Electrical connection (multi-pole, 25-pin, IP 65)

**HANSA FLEX**

## Właściwości

<b>Czynniki robocze</b>	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
<b>Ciśnienie pracy</b>	Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)
<b>ciśnienie sterujące</b>	3 - 7 bar
<b>Zakres temperatury</b>	-10 °C to +60 °C
<b>Przepływ</b>	200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8)
<b>liczba wysteroowań</b>	Max. 16 (e.g. 16 spring return valves)
<b>Pomocniczy napęd ręczny</b>	Latching (bistable), Monostable (non-latching) version also available on request
<b>Pobór mocy</b>	0.6 W per pilot
<b>rodzaj ochrony</b>	IP 65



## Wskazówka

Dalsze informacje na zapytanie.

## Opis

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

## Dodatkowe informacje

Important: The scope of supply does not include a connector. Please order separately.

## Artykuł

Oznaczenie	Definicja
K- 07 15 22 45	IP 67 connector, 25-pin, with 1 m cable
K- 07 15 22 46	IP 67 connector, 25-pin, with 2.5 m cable
K- 07 15 22 47	IP 67 connector, 25-pin, with 5 m cable