

K-LKM S NW7,4 DREH IG VA

Safety couplings DN 7.4, stainless steel 1.4404, female, swivel type

HANSA FLEX

Właściwości

Ciśnienie robocze	maks. 10 bar
przepływ powietrza	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Temperatura czynnika	-20 °C to +150 °C
Obudowa	Stainless steel 1.4404
gwint	Stainless steel 1.4404
części wewnętrzne	Stainless steel 1.4404
gałka, zawór	Stainless steel 1.4404
Materiał uszczelniający	FKM



Wskazówka

Not suitable for hitting / pulsating tools.

Dalsze informacje na zapytanie.

Opis

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Dodatkowe informacje

Not suitable for hitting / pulsating tools.

Artykuł

Oznaczenie	Przyłącze	Długość (mm)	SW (mm)
K- 07 35 12 79	G 1/4 female	71,5	21
K- 07 35 12 80	G 3/8 female	75,5	21
K- 07 35 12 81	G 1/2 female	77,5	24