K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

Właściwości

Przeznaczenie	Air, gases, oils, greases, fuels, organic and inorganic substances
Temperatura robocza	-40 °C to +100 °C
Rodzaj przyłącza	connection nipples and coupling NW 7,2



Wskazówka

Dalsze informacje na zapytanie.

Opis

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Artykuł

Oznaczenie	Ø wewn. wąż (mm)	Ø zewn. wąż (mm)	Ø zewn. spirala (mm)	zwoje	Max. working pressure resistance at 23°C (bar)	maks. długość robocza (m)
K- 07 10 12 95	6,3	7,9	75	15	13	2,5
K- 07 10 12 96	6,3	7,9	75	30	13	5,0
K- 07 10 12 97	6,3	7,9	75	45	13	7,5
K- 07 10 12 65	7,9	9,5	115	10	12	2,5
K- 07 10 12 66	7,9	9,5	115	20	12	5,0
K- 07 10 12 67	7,9	9,5	115	30	12	7,5
K- 07 10 12 68	9,5	11,8	140	8	11	2,5
K- 07 10 12 69	9,5	11,8	140	15	11	5,0
K- 07 10 12 70	9,5	11,8	140	23	11	7,5

Akcesoria

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector

Mimo starannego sprawdzenia nie możemy wykluczyć błędów i nie gwarantujemy prawidłowości podanych informacji.