

# K-SPIR SCHL KUPPL SET LKM NW 7,4

Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel

**HANSA FLEX**

## Właściwości

Rodzaj przyłącza	with pushbutton safety coupling NW 7,4 steel nipple galvanised
Temperatura robocza	-40 °C to +74 °C



## Wskazówka

Dalsze informacje na zapytanie.

## Opis

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Nie nadaje się do narzędzi uderowych lub impulsowych!

## Artykuł

Oznaczenie	Ø wewn. wąż (mm)	Ø zewn. wąż (mm)	Ø zwój zewnętrzny (mm)	Max. working pressure resistance at 23°C (bar)	maks. długość robocza (m)
K- 07 10 12 71	5,0	8,0	40	10	3,0
K- 07 10 12 73	5,0	8,0	40	10	6,0
K- 07 10 12 75	5,0	8,0	40	10	7,5
K- 07 10 12 80	6,3	9,5	60	10	3,0
K- 07 10 12 82	6,3	9,5	60	10	6,0
K- 07 10 12 84	6,3	9,5	60	10	7,5
K- 07 10 12 78	6,3	9,5	60	10	10,0
K- 07 10 12 89	8,0	12,0	80	9	3,0
K- 07 10 12 91	8,0	12,0	80	9	6,0
K- 07 10 12 93	8,0	12,0	80	9	7,5
K- 07 10 12 87	8,0	12,0	80	9	10,0

## Akcesoria

K-DREHBARE VERSCHRAUBUNG Swivel adapters