# K-SPIR SCHL KUPPL SET LKM NW 7,4

Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel

## Właściwości

| | |
|---|---|
| **Rodzaj przyłącza** | with pushbutton safety coupling NW 7,4 steel nipple galvanised |
| **Temperatura robocza** | -40 °C to +74 °C |



## Wskazówka

Dalsze informacje na zapytanie.

## Opis

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.
Nie nadaje się do narzędzi udarowych lub impulsowych!

## Artykuł

| Oznaczenie | Ø wewn. wąż (mm) | Ø zewn. wąż (mm) | Ø zwój zewnętrzny (mm) | Max. working pressure resistance at 23°C (bar) | maks. długość robocza (m) |
|---|---|---|---|---|---|
| **K- 07 10 12 71** | 5,0 | 8,0 | 40 | 10 | 3,0 |
| **K- 07 10 12 73** | 5,0 | 8,0 | 40 | 10 | 6,0 |
| **K- 07 10 12 75** | 5,0 | 8,0 | 40 | 10 | 7,5 |
| **K- 07 10 12 80** | 6,3 | 9,5 | 60 | 10 | 3,0 |
| **K- 07 10 12 82** | 6,3 | 9,5 | 60 | 10 | 6,0 |
| **K- 07 10 12 84** | 6,3 | 9,5 | 60 | 10 | 7,5 |
| **K- 07 10 12 78** | 6,3 | 9,5 | 60 | 10 | 10,0 |
| **K- 07 10 12 89** | 8,0 | 12,0 | 80 | 9 | 3,0 |
| **K- 07 10 12 91** | 8,0 | 12,0 | 80 | 9 | 6,0 |
| **K- 07 10 12 93** | 8,0 | 12,0 | 80 | 9 | 7,5 |
| **K- 07 10 12 87** | 8,0 | 12,0 | 80 | 9 | 10,0 |

## Akcesoria

| | |
|---|---|
| **K-DREHBARE VERSCHRAUBUNG** | Swivel adapters |

*Mimo starannego sprawdzenia nie możemy wykluczyć błędów i nie gwarantujemy prawidłowości podanych informacji.*