

# K-W90 DRV AS-FS

Speed controllers, 90°, connection plug, with built-in indicator

**HANSA FLEX**

## Właściwości

|                                      |   |
|--------------------------------------|---|
| <b>maks. ciśnienie robocze</b>       | 1 MPa   |
| <b>min. ciśnienie robocze</b>        | 0.10 MPa  |
| <b>odgałęzienia</b>                  | 1   |
| <b>liczba przewodów zasilających</b> | 1   |
| <b>wyrównanie okno wskazujące</b>    | 0°  |
| <b>kolor gałki obrotowej</b>         | Blue  |
| <b>Ciśnienie kontrolne</b>           | 1,50 MPa  |
| <b>Sterowanie</b>                    | Flow governing  |
| <b>Temperatura czynnika</b>          | -5 °C to +60 °C (ohne Gefrieren)  |
| <b>temperatura otoczenia</b>         | -5 °C bis +60 °C (no freezing)  |
| <b>Czynniki robocze</b>              | sprężone powietrze  |
| <b>Materiał węży</b>                 | polyamid, soft polyamid, polyurethane, FEP, PFA   |
| <b>seria</b>                         | AS-FS   |
| <b>Dalsze informacje</b>             | large rotary knob with push-lock latch<br>larger free space under the hose<br>Lockable rotary knob, numeric display |



## Artykuł

| Oznaczenie     | Typowielkość | odgałęzienie przyłącza | przyłącze przewodu zasilającego | Wykonanie                 | obroty igły | Ciężar na mb<br>(kg) |
|----------------|--------------|------------------------|---------------------------------|---------------------------|-------------|----------------------|
| K- 07 30 30 54 | 1            | for hose outer-Ø2 mm   | outer thread M 5                | with sealing ring         | 8           | 0,007                |
| K- 07 30 30 57 | 1            | for hose outer-Ø3.2 mm | outer thread M 5                | with sealing ring         | 8           | 0,007                |
| K- 07 30 30 55 | 1            | for hose outer-Ø4 mm   | outer thread M 5                | with sealing ring         | 8           | 0,007                |
| K- 07 30 30 56 | 1            | for hose outer-Ø6 mm   | outer thread M 5                | with sealing ring         | 8           | 0,008                |
| K- 07 30 30 62 | 2            | for hose outer-Ø3.2 mm | outer thread R 1/8              | Teflon coated             | 10          | 0,007                |
| K- 07 30 30 67 | 2            | for hose outer-Ø3.2 mm | outer thread R 1/4              | Teflon coated             | 10          | 0,023                |
| K- 07 30 30 58 | 2            | for hose outer-Ø4 mm   | outer thread R 1/8              | Teflon coated             | 10          | 0,013                |
| K- 07 30 30 63 | 2            | for hose outer-Ø4 mm   | outer thread R 1/4              | Teflon coated             | 10          | 0,023                |
| K- 07 30 30 59 | 2            | for hose outer-Ø6 mm   | outer thread R 1/8              | Teflon coated             | 10          | 0,014                |
| K- 07 30 30 68 | 2            | for hose outer-Ø6 mm   | outer thread G 1/8              | surface with sealing ring | 10          | 0,014                |
| K- 07 30 30 64 | 2            | for hose outer-Ø6 mm   | outer thread R 1/4              | Teflon coated             | 10          | 0,023                |
| K- 07 30 30 69 | 2            | for hose outer-Ø6 mm   | outer thread G 1/4              | surface with sealing ring | 10          | 0,023                |
| K- 07 30 30 60 | 2            | for hose outer-Ø8 mm   | outer thread R 1/8              | Teflon coated             | 10          | 0,015                |
| K- 07 30 30 65 | 2            | for hose outer-Ø8 mm   | outer thread R 1/4              | Teflon coated             | 10          | 0,024                |
| K- 07 30 30 70 | 2            | for hose outer-Ø8 mm   | outer thread G 1/4              | surface with sealing ring | 10          | 0,024                |
| K- 07 30 30 61 | 2            | for hose outer-Ø10 mm  | outer thread R 1/8              | Teflon coated             | 10          | 0,016                |
| K- 07 30 30 66 | 2            | for hose outer-Ø10 mm  | outer thread R 1/4              | Teflon coated             | 10          | 0,025                |
| K- 07 30 30 71 | 2            | for hose outer-Ø10 mm  | outer thread G 1/4              | surface with sealing ring | 10          | 0,025                |
| K- 07 30 30 72 | 3            | for hose outer-Ø6 mm   | outer thread R 3/8              | Teflon coated             | 10          | 0,038                |
| K- 07 30 30 76 | 3            | for hose outer-Ø6 mm   | outer thread G 3/8              | surface with sealing ring | 10          | 0,038                |
| K- 07 30 30 73 | 3            | for hose outer-Ø8 mm   | outer thread R 3/8              | Teflon coated             | 10          | 0,038                |
| K- 07 30 30 77 | 3            | for hose outer-Ø8 mm   | outer thread G 3/8              | surface with sealing ring | 10          | 0,038                |
| K- 07 30 30 74 | 3            | for hose outer-Ø10 mm  | outer thread R 3/8              | Teflon coated             | 10          | 0,029                |
| K- 07 30 30 78 | 3            | for hose outer-Ø10 mm  | outer thread G 3/8              | surface with sealing ring | 10          | 0,029                |
| K- 07 30 30 75 | 3            | for hose outer-Ø12 mm  | outer thread R 3/8              | Teflon coated             | 10          | 0,041                |
| K- 07 30 30 79 | 4            | for hose outer-Ø10 mm  | outer thread R 1/2              | Teflon coated             | 10          | 0,062                |
| K- 07 30 30 82 | 4            | for hose outer-Ø10 mm  | outer thread G 1/2              | surface with sealing ring | 10          | 0,062                |
| K- 07 30 30 80 | 4            | for hose outer-Ø12 mm  | outer thread R 1/2              | Teflon coated             | 10          | 0,064                |
| K- 07 30 30 83 | 4            | for hose outer-Ø12 mm  | outer thread G 1/2              | surface with sealing ring | 10          | 0,064                |
| K- 07 30 30 81 | 4            | for hose outer-Ø16 mm  | outer thread R 1/2              | Teflon coated             | 10          | 0,068                |
| K- 07 30 30 84 | 4            | for hose outer-Ø16 mm  | outer thread G 1/2              | surface with sealing ring | 10          | 0,068                |