

# RB

## Curva de tubo 90°

### Características

|                        |                          |
|------------------------|--------------------------|
| Tipo                   | Curva de tubo 90°        |
| Norma                  | DIN 2391/C               |
| Material               | Aço ST 37.4 NBK (1.0255) |
| Proteção de superfície | fosfatado e oleado       |



### Descrição

Curvas de tubo 90° sem costura para perdas mínimas de fluxo.

### Artigo

| Descrição | Ø externo do tubo (mm) | Ø interno (mm) | S (mm) | Raio de curvatura R (mm) | a (mm) | b (mm) | L1 (mm) | L2 (mm) |
|-----------|------------------------|----------------|--------|--------------------------|--------|--------|---------|---------|
| RB 14-1.5 | 14,0                   | 11,0           | 1,50   | 30                       | 200,0  | 40,0   | 230,0   | 70,0    |
| RB 15-1.5 | 15,0                   | 12,0           | 1,50   | 30                       | 200,0  | 40,0   | 230,0   | 70,0    |
| RB 15-2   | 15,0                   | 11,0           | 2,00   | 30                       | 200,0  | 40,0   | 230,0   | 70,0    |
| RB 16-2   | 16,0                   | 12,0           | 2,00   | 30                       | 200,0  | 40,0   | 230,0   | 70,0    |
| RB 18-1.5 | 18,0                   | 15,0           | 1,50   | 36                       | 200,0  | 35,0   | 236,0   | 71,0    |
| RB 18-2   | 18,0                   | 14,0           | 2,00   | 36                       | 200,0  | 35,0   | 236,0   | 72,0    |
| RB 20-2   | 20,0                   | 16,0           | 2,00   | 36                       | 200,0  | 45,0   | 236,0   | 81,0    |
| RB 20-2.5 | 20,0                   | 15,0           | 2,50   | 36                       | 200,0  | 45,0   | 236,0   | 81,0    |
| RB 20-3   | 20,0                   | 14,0           | 3,00   | 36                       | 200,0  | 45,0   | 236,0   | 81,0    |
| RB 22-1.5 | 22,0                   | 19,0           | 1,50   | 38                       | 200,0  | 40,0   | 238,0   | 78,0    |
| RB 22-2   | 22,0                   | 18,0           | 2,00   | 38                       | 200,0  | 40,0   | 238,0   | 78,0    |
| RB 22-2.5 | 22,0                   | 17,0           | 2,50   | 38                       | 200,0  | 40,0   | 238,0   | 78,0    |
| RB 22-3.5 | 22,0                   | 15,0           | 3,50   | 38                       | 200,0  | 40,0   | 238,0   | 78,0    |
| RB 25-2   | 25,0                   | 21,0           | 2,00   | 44                       | 200,0  | 50,0   | 244,0   | 94,0    |
| RB 25-2.5 | 25,0                   | 20,0           | 2,50   | 44                       | 200,0  | 50,0   | 244,0   | 94,0    |
| RB 25-3   | 25,0                   | 19,0           | 3,00   | 44                       | 200,0  | 50,0   | 244,0   | 94,0    |
| RB 25-4   | 25,0                   | 17,0           | 4,00   | 44                       | 200,0  | 50,0   | 244,0   | 94,0    |
| RB 28-1.5 | 28,0                   | 25,0           | 1,50   | 48                       | 200,0  | 50,0   | 248,0   | 98,0    |
| RB 28-2   | 28,0                   | 24,0           | 2,00   | 48                       | 200,0  | 50,0   | 248,0   | 98,0    |
| RB 28-3   | 28,0                   | 22,0           | 3,00   | 48                       | 200,0  | 50,0   | 248,0   | 98,0    |
| RB 30-2.5 | 30,0                   | 25,0           | 2,50   | 50                       | 200,0  | 60,0   | 250,0   | 110,0   |
| RB 30-3   | 30,0                   | 24,0           | 3,00   | 50                       | 200,0  | 60,0   | 250,0   | 110,0   |
| RB 30-4   | 30,0                   | 22,0           | 4,00   | 50                       | 200,0  | 60,0   | 250,0   | 110,0   |
| RB 35-2   | 35,0                   | 31,0           | 2,00   | 60                       | 200,0  | 65,0   | 260,0   | 125,0   |
| RB 35-3   | 35,0                   | 29,0           | 3,00   | 60                       | 200,0  | 65,0   | 260,0   | 125,0   |
| RB 38-2.5 | 38,0                   | 33,0           | 2,50   | 65                       | 200,0  | 75,0   | 265,0   | 140,0   |
| RB 38-3   | 38,0                   | 32,0           | 3,00   | 65                       | 200,0  | 75,0   | 265,0   | 140,0   |
| RB 38-4   | 38,0                   | 30,0           | 4,00   | 65                       | 200,0  | 75,0   | 265,0   | 140,0   |
| RB 38-5   | 38,0                   | 28,0           | 5,00   | 65                       | 200,0  | 75,0   | 265,0   | 140,0   |
| RB 42-2   | 42,0                   | 38,0           | 2,00   | 80                       | 200,0  | 85,0   | 280,0   | 165,0   |
| RB 42-3   | 42,0                   | 36,0           | 3,00   | 80                       | 200,0  | 85,0   | 280,0   | 165,0   |
| RB 50-6   | 50,0                   | 38,0           | 6,00   | 210                      | 100,0  | 100,0  | 310,0   | 310,0   |
| RB 65-8   | 65,0                   | 49,0           | 8,00   | 210                      | 110,0  | 110,0  | 320,0   | 320,0   |
| RB 80-10  | 80,0                   | 60,0           | 10,00  | 150                      | 120,0  | 120,0  | 330,0   | 330,0   |