


Características			
Conexão 1	Rosca fêmea ORFS		
Tipo de vedação 1	face plana		
Conexão 2	Rosca externa UN/UNF		
Tipo de vedação 2	Cone externo 74°		
Tipo	União macho x fêmea		
Modelo	reto		
Material	Aço		
Proteção de superfície	com revestimento galvanizado		





G1	G2	SW (mm)	S1
9/16" -18 UNF	7/16" -20 UNF	17	19
11/16" -16 UN	9/16" -18 UNF	19	22
13/16" -16 UN	3/4" -16 UNF	22	24
1" -14 UNS	7/8" -14 UNF	27	30
1.3/16" -12 UN	1.1/16" -12 UN	32	36
1.7/16" -12 UN	1.5/16" -12 UN	41	41
	9/16" -18 UNF 11/16" -16 UN 13/16" -16 UN 1" -14 UNS 1.3/16" -12 UN	9/16" -18 UNF 7/16" -20 UNF 11/16" -16 UN 9/16" -18 UNF 13/16" -16 UN 3/4" -16 UNF 1" -14 UNS 7/8" -14 UNF 1.3/16" -12 UN 1.1/16" -12 UN	9/16" -18 UNF 7/16" -20 UNF 17 11/16" -16 UN 9/16" -18 UNF 19 13/16" -16 UN 3/4" -16 UNF 22 1" -14 UNS 7/8" -14 UNF 27 1.3/16" -12 UN 1.1/16" -12 UN 32

SW, S1, S2 = tamanho da chave