

# SF O-RING V

O-ring, 90SH FKM (FPM)

## Características

|                  |                     |
|------------------|---------------------|
| Tipo             | Forma retangular    |
| Temperatura min. | -15 °C              |
| Temperatura max. | 200 °C              |
| Material         | FKM SH 90 ( Viton ) |



## Artigo

| Descrição     | DN* | Tamanho | Polegada | Ø d1 (mm) | Ø d2 (mm) | S (mm) |
|---------------|-----|---------|----------|-----------|-----------|--------|
| SF ORING 13 V | 12  | 8       | 1/2"     | 18,66     | 25,72     | 3,53   |
| SF ORING 20 V | 19  | 12      | 3/4"     | 24,99     | 32,05     | 3,53   |
| SF ORING 25 V | 25  | 16      | 1"       | 32,92     | 39,98     | 3,53   |
| SF ORING 32 V | 31  | 20      | 1.1/4"   | 37,70     | 44,76     | 3,53   |
| SF ORING 40 V | 38  | 24      | 1.1/2"   | 47,22     | 54,28     | 3,53   |
| SF ORING 50 V | 51  | 32      | 2"       | 56,74     | 63,80     | 3,53   |
| SF ORING 60 V | 60  | 40      | 2.1/2"   | 69,45     | 76,51     | 3,53   |
| SF ORING 75 V | 76  | 48      | 3"       | 85,32     | 92,38     | 3,53   |

## Variantes do produto

SF O-RING PU