

2 OK VA

Abraçadeira de dois olhais

HANSA FLEX

Características

Campo de aplicação Fixações de mangueira na área de baixa pressão

Material Aço inoxidável



Artigo

Descrição	Faixa de fixação (mm)	Largura da fita (mm)
2 OK 3-5 VA	3,4 - 5,0	5,0
2 OK 3.1-4.1 VA	3,1 - 4,1	3,5
2 OK 3.5-4.5 VA	3,5 - 4,5	3,5
2 OK 5-7 VA	5,0 - 7,0	6,0
2 OK 7-9 VA	7,0 - 9,0	6,0
2 OK 8-11 VA	8,0 - 11,0	7,0
2 OK 9-11 VA	9,0 - 11,0	6,5
2 OK 11-13 VA	11,0 - 13,0	6,5
2 OK 13-15 VA	13,0 - 15,0	7,0
2 OK 15-17 VA	15,0 - 17,0	7,5
2 OK 15-18 VA	15,0 - 18,0	7,5
2 OK 17-20 VA	17,0 - 20,0	7,5
2 OK 18-21 VA	18,0 - 21,0	8,0
2 OK 19-22 VA	18,1 - 22,0	9,0
2 OK 20-23 VA	20,0 - 23,0	8,0
2 OK 22-25 VA	22,0 - 25,0	8,5
2 OK 23-27 VA	23,0 - 27,0	8,5
2 OK 25-28 VA	25,0 - 28,0	9,0
2 OK 27-31 VA	26,3 - 31,0	10,0
2 OK 28-31 VA	28,0 - 31,0	9,0
2 OK 31-34 VA	31,0 - 34,0	9,5
2 OK 34-37 VA	34,0 - 37,0	9,5
2 OK 37-40 VA	37,0 - 40,0	10,0
2 OK 40-43 VA	40,0 - 43,0	10,0
2 OK 43-46 VA	43,0 - 46,0	10,0

Variantes do produto

2 OK Abraçadeira de dois olhais, com revestimento galvanizado

2 OK VC Abraçadeira de dois olhais, galvanizado cromado brilhante