

2 OK VA

Abraçadeira de dois olhais

HANSA FLEX

Características

Campo de aplicação	Fixações de mangueira na área de baixa pressão
Material	Aço inoxidável



Artigo

Descrição	Faixa de fixação (mm)	Largura da fita (mm)
2 OK 3-5 VA	3,4 - 5,0	5,0
2 OK 3.1-4.1 VA	3,1 - 4,1	3,5
2 OK 3.5-4.5 VA	3,5 - 4,5	3,5
2 OK 5-7 VA	5,0 - 7,0	6,0
2 OK 7-9 VA	7,0 - 9,0	6,0
2 OK 8-11 VA	8,0 - 11,0	7,0
2 OK 9-11 VA	9,0 - 11,0	6,5
2 OK 11-13 VA	11,0 - 13,0	6,5
2 OK 13-15 VA	13,0 - 15,0	7,0
2 OK 15-17 VA	15,0 - 17,0	7,5
2 OK 15-18 VA	15,0 - 18,0	7,5
2 OK 17-20 VA	17,0 - 20,0	7,5
2 OK 18-21 VA	18,0 - 21,0	8,0
2 OK 19-22 VA	18,1 - 22,0	9,0
2 OK 20-23 VA	20,0 - 23,0	8,0
2 OK 22-25 VA	22,0 - 25,0	8,5
2 OK 23-27 VA	23,0 - 27,0	8,5
2 OK 25-28 VA	25,0 - 28,0	9,0
2 OK 27-31 VA	26,3 - 31,0	10,0
2 OK 28-31 VA	28,0 - 31,0	9,0
2 OK 31-34 VA	31,0 - 34,0	9,5
2 OK 34-37 VA	34,0 - 37,0	9,5
2 OK 37-40 VA	37,0 - 40,0	10,0
2 OK 40-43 VA	40,0 - 43,0	10,0
2 OK 43-46 VA	43,0 - 46,0	10,0

Variantes do produto

2 OK	Abraçadeira de dois olhais, com revestimento galvanizado
2 OK VC	Abraçadeira de dois olhais, galvanizado cromado brilhante