

### Características

<b>Tipos</b>	Abraçadeira de rosca sem fim
<b>Complemento de tipo</b>	Parafuso sextavado com fenda
<b>Material</b>	Aço inoxidável 1.4436



### Artigo

Descrição	Faixa de fixação (mm)	Largura da fita (mm)
<b>ESK 08-14 W5</b>	8 - 14	9,0
<b>ESK 11-17 W5</b>	11 - 17	9,0
<b>ESK 13-20 W5</b>	13 - 20	9,0
<b>ESK 15-24 W5</b>	15 - 24	9,0
<b>ESK 19-28 W5</b>	19 - 28	12,0
<b>ESK 22-32 W5</b>	22 - 32	12,0
<b>ESK 26-38 W5</b>	26 - 38	12,0
<b>ESK 32-44 W5</b>	32 - 44	12,0
<b>ESK 38-50 W5</b>	38 - 50	12,0
<b>ESK 44-56 W5</b>	44 - 56	12,0
<b>ESK 50-65 W5</b>	50 - 65	12,0
<b>ESK 58-75 W5</b>	58 - 75	12,0
<b>ESK 68-85 W5</b>	68 - 85	12,0
<b>ESK 77-95 W5</b>	77 - 95	12,0
<b>ESK 87-112 W5</b>	87 - 112	12,0
<b>ESK 104-138 W5</b>	104 - 138	12,0
<b>ESK 130-165 W5</b>	130 - 165	12,0
<b>ESK 150-180 W5</b>	150 - 180	12,0
<b>ESK 175-205 W5</b>	175 - 205	12,0
<b>ESK 200-231 W5</b>	200 - 231	12,0
<b>ESK 226-256 W5</b>	226 - 256	12,0
<b>ESK 251-282 W5</b>	251 - 282	12,0
<b>ESK 277-307 W5</b>	277 - 307	12,0

### Variantes do produto

ESK

### Acessórios

<b>SCHRAUBENDR</b>	Chave de fenda, flexível
--------------------	--------------------------