

K-PUR-BREMSSPIRALE

PUR brake coil with connection

HANSA FLEX

Características

Conexão 1 + 2	Rosca externa métrica cilíndrica
Norma	testado conforme DIN 74323 DIN 74324 ISO 7268-2 ISO 7375-2 DIN 73378 DIN 74310-2
Homologação	German Technical Surveyance Association (TÜV)- type approved (Certificate R 9910199)
Temperatura min.	-40 °C
Temperatura max.	90 °C
Material	PUR



Informações adicionais

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

Artigo

Descrição	G1 + G2	Ø interno (mm)	Ø externo (mm)	Espessura da parede (mm)	Comprimento (m)	Cor
K- 07 10 13 21	M 16 x 1,5	8,0	12,0	2,0	4,50	preto
K- 07 10 13 22	M 16 x 1,5	8,0	12,0	2,0	4,50	amarelo
K- 07 10 13 23	M 16 x 1,5	8,0	12,0	2,0	4,50	vermelho
K- 07 10 13 24	M 16 x 1,5	8,0	12,0	2,0	5,50	preto
K- 07 10 13 25	M 16 x 1,5	8,0	12,0	2,0	5,50	amarelo
K- 07 10 13 26	M 16 x 1,5	8,0	12,0	2,0	5,50	vermelho