K-DMUF GENAUIGKEIT 0,2%

Pressure transmitters, accuracy 0.2% of span

HANSA FLEX

Características

Tipo	S-10
Tensão	Non-stabilised 10/30 V DC voltage
Conexão elétrica	With right-angle connector acc. to DIN EN 175301-803 A
Tipo de proteção	IP 65 acc. to EN 60529
Sinal de saída	4 to 20 mA, 2-wire
Falta de linearidade	0.2% of span
Temperatura do fluido	-30 °C to +100 °C
Temperatura ambiente	-20 °C to +80 °C
Peças que entraram em contato com o material de medição	CrNi steel 1.4571
Carcaça	CrNi steel 1.4571



Descrição

Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

Informações adicionais

Further measuring ranges on request

Pressure converter with flush-mounted membrane for measuring highly viscous and crystalline media on request.

Artigo

Descrição	Faixa de medição	Rosca
K- 07 20 10 30	-1 / 0.0 bar	G 1/2
K- 07 20 10 31	0 - 0.25 bar	G 1/2
K- 07 20 10 32	0 - 0.4 bar	G 1/2
K- 07 20 10 33	0 - 1.0 bar	G 1/2
K- 07 20 10 34	0 - 4.0 bar	G 1/2
K- 07 20 10 35	0 - 6.0 bar	G 1/2
K- 07 20 10 36	0 - 10.0 bar	G 1/2
K- 07 20 10 37	0 - 16.0 bar	G 1/2
K- 07 20 10 38	0 - 25.0 bar	G 1/2
K- 07 20 10 39	0 - 40.0 bar	G 1/2
K- 07 20 10 40	0 - 60.0 bar	G 1/2
K- 07 20 10 41	0 - 100.0 bar	G 1/2
K- 07 20 10 42	0 - 160.0 bar	G 1/2
K- 07 20 10 43	0 - 250.0 bar	G 1/2
K- 07 20 10 44	0 - 400.0 bar	G 1/2
K- 07 20 10 45	0 - 600.0 bar	G 1/2

Apesar de uma verificação cuidadosa, não podemos excluir a possibilidade de erros e não assumimos qualquer responsabilidade pelos dados aqui contidos.