

# K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

**HANSA FLEX**

## Características

|                         |                                                                                       |
|-------------------------|---------------------------------------------------------------------------------------|
| Temperatura operacional | -60 °C to +100 °C (PA 12)                                                             |
| Características         | Resistant to corrosion, vibration, impact, ageing, high pressures and heat            |
| Comprimento do tubo     | 3 m                                                                                   |
| Unidade de embalagem    | 10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units! |
| Material                | Polyamid PA 12, hard (according to DIN 73378)                                         |



## Nota

Operating pressure with 2.5 x overpressure safety!  
Outras indicações a pedido.

## Descrição

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## Artigo

| Descrição      | Ø externo do tubo (mm) | Ø interno do tubo (mm) | Pressão de serviço máx. com 20°C (bar) | Cor   |
|----------------|------------------------|------------------------|----------------------------------------|-------|
| K- 07 10 04 57 | 12                     | 9                      | 38                                     | azul  |
| K- 07 10 04 59 | 12                     | 9                      | 38                                     | preto |
| K- 07 10 04 61 | 15                     | 12                     | 25                                     | azul  |
| K- 07 10 04 63 | 15                     | 12                     | 25                                     | preto |
| K- 07 10 04 65 | 18                     | 14                     | 28                                     | azul  |
| K- 07 10 04 67 | 18                     | 14                     | 28                                     | preto |
| K- 07 10 04 69 | 22                     | 18                     | 22                                     | azul  |
| K- 07 10 04 71 | 22                     | 18                     | 22                                     | preto |
| K- 07 10 04 73 | 28                     | 23                     | 20                                     | azul  |
| K- 07 10 04 75 | 28                     | 23                     | 20                                     | preto |