# K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

## Características

| | |
|---|---|
| **Temperatura operacional** | -60 °C to +100 °C (PA 12) |
| **Características** | Resistant to corrosion, vibration, impact, ageing, high pressures and heat |
| **Comprimento do tubo** | 3 m |
| **Unidade de embalagem** | 20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units! |
| **Material** | Polyamid PA 12, hard (according to DIN 73378) |



## Nota

Operating pressure with 2.5 x overpressure safety!
Outras indicações a pedido.

## Descrição

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## Artigo

| Descrição | Ø externo do tubo (mm) | Ø interno do tubo (mm) | Pressão de serviço máx. com 20°C (bar) | Cor |
|---|---|---|---|---|
| **K- 07 10 04 56** | 12 | 9 | 38 | azul |
| **K- 07 10 04 58** | 12 | 9 | 38 | preto |
| **K- 07 10 04 60** | 15 | 12 | 25 | azul |
| **K- 07 10 04 62** | 15 | 12 | 25 | preto |
| **K- 07 10 04 64** | 18 | 14 | 28 | azul |
| **K- 07 10 04 66** | 18 | 14 | 28 | preto |
| **K- 07 10 04 68** | 22 | 18 | 22 | azul |
| **K- 07 10 04 70** | 22 | 18 | 22 | preto |
| **K- 07 10 04 72** | 28 | 23 | 20 | azul |
| **K- 07 10 04 74** | 28 | 23 | 20 | preto |

*Apesar de uma verificação cuidadosa, não podemos excluir a possibilidade de erros e não assumimos qualquer responsabilidade pelos dados aqui contidos.*