K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

Características

Temperatura operacional	-60 °C to +100 °C (PA 12)
Características	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Comprimento do tubo	3 m
Unidade de embalagem	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Material	Polyamid PA 12, hard (according to DIN 73378)



Nota

Operating pressure with 2.5 x overpressure safety!
Outras indicações a pedido.

Descrição

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Artigo

Descrição	Ø externo do tubo (mm)	Ø interno do tubo (mm)	Pressão de serviço máx. com 20°C (bar)	Cor
K- 07 10 04 56	12	9	38	azul
K- 07 10 04 58	12	9	38	preto
K- 07 10 04 60	15	12	25	azul
K- 07 10 04 62	15	12	25	preto
K- 07 10 04 64	18	14	28	azul
K- 07 10 04 66	18	14	28	preto
K- 07 10 04 68	22	18	22	azul
K- 07 10 04 70	22	18	22	preto
K- 07 10 04 72	28	23	20	azul
K- 07 10 04 74	28	23	20	preto

Apesar de uma verificação cuidadosa, não podemos excluir a possibilidade de erros e não assumimos qualquer responsabilidade pelos dados aqui contidos.