K-SPIR SCHL B DREH VERSCHRAU

Spiral hose, with swivel adapter fitted at both ends and kink protector

Características

Aplicação	Air, gases, oils, greases, fuels, organic and inorganic substances
Temperatura operacional	-40 °C to +100 °C
Tipo de conexão	connection nipples and coupling NW 7,2



Nota

Outras indicações a pedido.

Descrição

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Artigo

Descrição	Ø interno da mangueira (mm)	Ø externo da mangueira (mm)	Rosca	Ø externo da espiral (mm)	Torções	Max. working pressure resistance at 23°C (bar)	Comprimento de trabalho máx. (m)
K- 07 10 07 34	3,1	4,7	R 1/8	38	36	22	2,5
K- 07 10 07 35	3,1	4,7	R 1/8	38	72	22	5,0
K- 07 10 07 36	3,1	4,7	R 1/8	38	108	22	7,5
K- 07 10 07 37	4,8	6,3	R 1/4	75	15	16	2,5
K- 07 10 07 38	4,8	6,3	R 1/4	75	30	16	5,0
K- 07 10 07 39	4,8	6,3	R 1/4	75	45	16	7,5
K- 07 10 07 40	6,3	7,9	R 1/4	75	15	13	2,5
K- 07 10 07 41	6,3	7,9	R 1/4	75	30	13	5,0
K- 07 10 07 42	6,3	7,9	R 1/4	75	45	13	7,5
K- 07 10 07 28	7,9	9,5	R 1/4	115	10	12	2,5
K- 07 10 07 29	7,9	9,5	R 1/4	115	20	12	5,0
K- 07 10 07 30	7,9	9,5	R 1/4	115	30	12	7,5
K- 07 10 07 31	9,5	11,8	R 3/8	140	8	11	2,5
K- 07 10 07 32	9,5	11,8	R 3/8	140	15	11	5,0
K- 07 10 07 33	9,5	11,8	R 3/8	140	23	11	7,5

Acessórios

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector

Apesar de uma verificação cuidadosa, não podemos excluir a possibilidade de erros e não assumimos qualquer responsabilidade pelos dados aqui contidos.