K-SPIR SCHL DREH VERSCHRAU

Spiral hose, with swivel adapter and kink protector

HANSA FLEX

Características

Temperatura operacional	-40 °C to +74 °C



Nota

Outras indicações a pedido.

Descrição

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Artigo

Descrição	Rosca	Ø interno da mangueira (mm)	Ø externo da mangueira (mm)	Torção externa Ø (mm)	Max. working pressure resistance at 23°C (bar)	Comprimento de trabalho máx. (m)
K- 07 10 07 19	G 1/4	5,0	8,0	40	10	3,0
K- 07 10 07 20	G 1/4	5,0	8,0	40	10	6,0
K- 07 10 07 21	G 1/4	5,0	8,0	40	10	7,5
K- 07 10 07 22	G 1/4	6,3	9,5	60	10	3,0
K- 07 10 07 23	G 1/4	6,3	9,5	60	10	6,0
K- 07 10 07 24	G 1/4	6,3	9,5	60	10	7,5
K- 07 10 12 77	G 1/4	6,3	9,5	60	10	10,0
K- 07 10 07 25	G 3/8	8,0	12,0	80	9	3,0
K- 07 10 07 26	G 3/8	8,0	12,0	80	9	6,0
K- 07 10 07 27	G 3/8	8,0	12,0	80	9	7,5
K- 07 10 12 86	G 3/8	8,0	12,0	80	9	10,0

Acessórios

K-DREHBARE VERSCHRAUBUNG	Swivel adapters

Apesar de uma verificação cuidadosa, não podemos excluir a possibilidade de erros e não assumimos qualquer responsabilidade pelos dados aqui contidos.