K-VSEH 3-KRAFT

Receptacle combinations »3-Kraft«

Características

Carcaça	Amaplast with hinged cover
Integrado na carcaça	Hanging eyelets, wall mounting fixing and standing feet
Modelo	Pre-wired
Guias de cabos	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection or grabrails (all introductions to break)
Tipo de proteção	IP 44



Nota

Outras indicações a pedido.

Descrição

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Artigo

Descrição	Equipamento	Cor
K- 07 10 03 50	3 Schuko socket 16 A 2p + E 230 V	amarelo
K- 07 10 03 49	2 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	prata

Acessórios

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«

Apesar de uma verificação cuidadosa, não podemos excluir a possibilidade de erros e não assumimos qualquer responsabilidade pelos dados aqui contidos.