

# K-HYDR-KUPPLUNG IG POM

Hydraulic couplings, POM

**HANSA FLEX**

## Características

<b>Pressão operacional</b>	See table. All values referred to a medium temperature of 50 °C (static working pressure)
<b>Fluxo de ar</b>	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
<b>Temperatura do fluido</b>	-20 °C to +90 °C
<b>Carcaça, manga</b>	POM (Delrin), white
<b>Válvula</b>	Stainless steel 1.4305
<b>Mola, anel de trava, esferas</b>	stain less steel
<b>Material de vedação</b>	NBR



## Nota

Outras indicações a pedido.

## Descrição

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## Artigo

Descrição	Conexão	Pressão operacional (bar)	Comprimento (mm)	NW	SW (mm)
K- 07 35 03 76	G 1/8 female	15,0	48,5	4,3	14
K- 07 35 03 77	G 1/4 female	15,0	57,6	6,0	19
K- 07 35 03 78	G 3/8 female	15,0	64,2	7,5	22
K- 07 35 03 79	G 1/2 female	10,0	76,0	11,0	27
K- 07 35 03 80	G 3/4 female	10,0	96,0	13,0	34