

K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM

HANSA FLEX

Características

Pressão operacional	See table. All values referred to a medium temperature of 50 °C (static working pressure)
Fluxo de ar	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
Temperatura do fluido	-20 °C to +90 °C
Carcaça, manga	POM (Delrin), white
Válvula	Stainless steel 1.4305
Mola, anel de trava, esferas	stain less steel
Material de vedação	NBR



Nota

Outras indicações a pedido.

Descrição

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Artigo

Descrição	Conexão	Pressão operacional (bar)	Comprimento (mm)	NW	SW (mm)
K- 07 40 39 58	G 1/8 female	15,0	29,5	4,3	14
K- 07 40 39 59	G 1/4 female	15,0	35,3	6,0	19
K- 07 40 39 60	G 3/8 female	15,0	39,0	7,5	22
K- 07 40 39 61	G 1/2 female	10,0	48,0	11,0	27
K- 07 40 39 62	G 3/4 female	10,0	60,0	13,0	36