


K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

Características

Pressão operacional	0 - 35 bar, maximum static working pressure (non-pulsating)
Fluxo de ar	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura do fluido	-20 °C to +100 °C
Manga de desbloqueio	Anodised aluminium
Mola, anel de trava, esferas	stain less steel
Material de vedação	NBR



Nota

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings. Outras indicações a pedido.

Descrição

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artigo

Descrição	Conexão	Cor	Comprimento (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	verde	45,0	14
K- 07 35 06 81	G 1/4 male	verde	47,0	17
K- 07 35 06 82	G 1/8 female	verde	45,0	14
K- 07 35 06 83	G 1/4 female	verde	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	azul	45,0	14
K- 07 35 06 89	G 1/4 male	azul	47,0	17
K- 07 35 06 90	G 1/8 female	azul	45,0	14
K- 07 35 06 91	G 1/4 female	azul	47,0	17
K- 07 35 06 92	G 1/8 male	vermelho	45,0	14
K- 07 35 06 93	G 1/4 male	vermelho	47,0	17
K- 07 35 06 94	G 1/8 female	vermelho	45,0	14
K- 07 35 06 95	G 1/4 female	vermelho	47,0	17