
K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

Características

Pressão operacional	0 - 35 bar, maximum static working pressure (non-pulsating)
Fluxo de ar	1.800 l/min (at 6 bar and Δp = 0.5 bar)
Temperatura do fluido	-20 °C to +100 °C
Carcaça	Brass
Válvula	Die-cast zinc, nickel-plated
Manga de desbloqueio	Anodised aluminium
Mola, anel de trava, esferas	stain less steel
Material de vedação	NBR



Nota

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.
Outras indicações a pedido.

Descrição

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artigo

Descrição	Conexão	Cor	Comprimento (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	verde	57,5	19
K- 07 35 08 02	G 3/8 male	verde	57,5	19
K- 07 35 08 03	G 1/4 female	verde	55,5	19
K- 07 35 08 04	G 3/8 female	verde	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	azul	57,5	19
K- 07 35 08 10	G 3/8 male	azul	57,5	19
K- 07 35 08 11	G 1/4 female	azul	55,5	19
K- 07 35 08 12	G 3/8 female	azul	54,5	19
K- 07 35 08 13	G 1/4 male	vermelho	57,5	19
K- 07 35 08 14	G 3/8 male	vermelho	57,5	19
K- 07 35 08 15	G 1/4 female	vermelho	55,5	19
K- 07 35 08 16	G 3/8 female	vermelho	54,5	19

Apesar de uma verificação cuidadosa, não podemos excluir a possibilidade de erros e não assumimos qualquer responsabilidade pelos dados aqui contidos.