

K-INLINE-EJEKTOREN SLP

Inline ejectors »SLP«, plug connection

HANSA FLEX

Características

Características Vacuum generator with high maximum vacuum level (85% vacuum)
No moving parts, which means no wear and no maintenance
ultra small footprint, suitable for confined spaces
minimal air consumption
low noise

Aplicação by screwing / plugging into the distribution beam
direct attachment to the suction pad
for handling various workpieces

Carcaça plastic (Typ SLP)

Sistema do bocal Brass (type VR)

Conexão thread connector



Nota

Outras indicações a pedido.

Descrição

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

Artigo

Descrição	Tamanho do bocal	Conexão de saída de ar	Conexão de ar comprimido	Conexão de vácuo	Grau de evacuação	Consumo de ar Aspirar (L/min)	Capacidade de aspiração máx. (L/min)	Comprimento (mm)	Pressão operacional (bar)
K- 07 45 01 27	0,5	-	4 mm	4 mm	85 %	13,0	8,0	57,0	4,5
K- 07 45 01 28	0,7	-	4 mm	4 mm	85 %	25,0	16,0	57,0	4,5